TITLE OF THE INVENTION

IMAGE SEARCH METHOD AND APPARATUS

FIELD OF THE INVENTION

5   The present invention relates to an image search technique of searching for a desired still image, moving image, or the like in a computer, information processing equipment, or the like.

10   BACKGROUND OF THE INVENTION

Recently, various kinds of information have been digitized, and the digitized information have been managed by a computer, information processing equipment, or the like. At the advent of JPEG, MPEG-1,

15   MPEG-2, MPEG-4, and the like, image contents such as still images or moving images can be efficiently compressed/coded as digitized information. These image contents have been stored in a large amount and managed in the hard disk of a computer or information

20   processing equipment with an increase in hard disk capacity and a reduction in cost. When a large amount of image contents is stored in a hard disk or the like, it raises a question about how to make a search to find out a desired image from the large amount of image

25   contents.

In general, as a technique of searching for a desired image from a large amount of stored image

contents, a method is available, which assigns keywords
to the respective image contents in advance and
searches for a keyword assigned to images. A technique
of displaying the images corresponding to the keyword
5   as a search result on a monitor or the like is used,
which allows the operator to visually find out a
desired image from the displayed images.

In the present day in which the Internet has been
popularized, such a search technique using keywords is
10 also generally used in an image search system which a
content provider having a large amount of image
contents has prepared on the Internet to broadcast
images to consumers.

Likewise, a search system for images present on
15 the respective WWW (World Wide Web) pages provided by a
WWW search system also provides a means for searching
for images by a similar technique by associating the
keywords, obtained from file names of src attributes
with img tags in HTML files, character strings of alt
20 attributes, or the like, with images indicated by the
file names in the src attributes.

Fig. 7 is a view showing an example of a search
operation window in a conventional image search system.
As shown in Fig. 7, an image search window 701 is
25 mainly constituted by a search instruction area 702 and
search result display area 705. In the search
instruction area 702, a keyword input area 703 for

inputting a keyword and a search button 704 for issuing a search instruction are displayed. The operator inputs a keyword in the keyword input area 703 by using a keyboard, and clicks the search button 704 with a

5   mouse. With this operation, images associated with the keyword identical to the character string input in the keyword input area 703 are searched out, and thumbnails (reduced images) of the images obtained as a result of the search are displayed in the form of a list in the

10 search result display area 705 in the order of the decreasing similarities of the objects from thumbnails 706 and 707 to the thumbnail 708.

As another search method, the following method is available. Objects are extracted from images by

15 segmenting them using information such as edges and textures. Feature amounts of colors, shapes, and the like of the objects are stored as indexes in a database in correspondence with the images. At the time of a search, partial images of objects corresponding to the

20 above index are selected, and the feature amounts of the objects are compared with each other to obtain a similarity. In this case as well, there is a method of sequentially displaying thumbnails (reduced images) of the images obtained as a search result in the form of a

25 list in the search result display area 705 in the order of thumbnails 706, 707, and 708.

In a moving image search as well, a moving image

- 3 -

is segmented at scene changes, and a search is made for

a still image as a representative image of each scene

by a method similar to that described above, thereby

searching for a desired moving image scene.

5   In the above conventional search method, however,

the thumbnail images displayed in the search result

display area 705 are images obtained by simply and

directly reducing whole still images. Many such

reduced images are simply arranged in the search result

10 display area 705. For this reason, when a partial

image corresponding to a keyword input for a search,

i.e., a partial region of a thumbnail image, is to be

visually checked, it is not easy to search for a

partial image corresponding to an object corresponding

15 to the keyword. In addition, grasping the details of

the partial image corresponding to the object is not

easier than searching for it.

Fig. 8 is a view showing an example of a still

image registered in an image database. If, for

20 example, the size of a partial image corresponding to a

keyword is relatively small in the image, like a

partial image 803 corresponding to the "car" shown in

Fig. 8, the corresponding partial region is displayed

in a smaller size in the search result display area

25 705. It is therefore not easy to visually find out a

partial image corresponding to the keyword input in the

keyword input area 703. It is more difficult to grasp

the details of the partial image.

Assume that the thumbnail images obtained as a result of a search using a feature amount such as the color or shape of an object are to be displayed in the search result display area 705. In this case as well, if a partial image corresponding the object which is designated at the time of the search is relatively small in the image to be searched, it is not easy to find out a partial image corresponding to the object designated at the time of the search. It is also not easy to grasp the details of the partial image.

Assume that a search is to be made by using a feature amount such as the color or shape of an object. In this case, in particular, since there is no guarantee that a concept representing the meaning of an object designated at the time of a search will reliably match a concept representing a partial image found as a search result, if the detected partial image is relatively small in the thumbnail image, it is not easy to even grasp what it is. In many cases, therefore, it is difficult to search for a desired image.

In addition, as described above, in some cases, it is impossible to grasp a partial image up to the details. When, therefore, candidate images obtained as a search result are displayed in the form of a list, it may be difficult to determine, by comparing partial images in the candidate images which satisfy a search

condition, which one of the candidate images is a
desired image.

SUMMARY OF THE INVENTION

5   The present invention has been proposed to solve
the conventional problems, and has as its objects to
provide an image search method and apparatus which can
display a search result more suitably when images are
searched out upon designation of a keyword or object,
10   and efficiently search for a desired image in the
displayed search result.

In order to achieve the above object, an image
search apparatus according to the present invention
comprises image storage means for storing a plurality
15   of images, region information storage means for
storing partial images included in the respective
images stored in the image storage means in
correspondence with the respective images, and region
feature storage means for storing features of the
20   partial images stored in the region information storage
means in correspondence with the partial images,
comprising image feature designation means for
designating a feature of a search target image,
candidate image determination means for searching
25   features of partial images in the region feature
storage means on the basis of the feature of the image
which is designated by the image feature designation

- 6 -

means, and determining an image which is made to
correspond to a partial image obtained on the basis of
a search result as a candidate image from the images
stored in the image storage means and   search result
5   display means for displaying a reduced image of the
candidate image determined by the candidate image
determination means,   wherein the search result
display means displays a reduced image of the candidate
image upon enlarging the partial image included in the
10   candidate image.

In order to achieve the above object, an image
search apparatus according to the present invention
comprises image storage means for storing a plurality
of images, region information storage means for
15   storing partial images included in the respective
images stored in the image storage means in
correspondence with the respective images, and region
feature storage means for storing features of the
partial images stored in the region information storage
20   means in correspondence with the partial images,
comprising image feature designation means for
designating a feature of a search target image,
candidate image determination means for searching
features of partial images in the region feature
25   storage means on the basis of the feature of the image
which is designated by the image feature designation
means, and determining an image which is made to

- 7 -

correspond to a plurality of partial images obtained on

the basis of a search result as a candidate image from

the images stored in the image storage means and

search result display means for displaying a

5   reduced image of the candidate image determined by the

candidate image determination means, wherein the search

result display means displays a reduced image of the

candidate image upon enlarging the plurality of partial

images included in the candidate image.

10   In order to achieve the above object, an image

search apparatus according to the present invention

comprises image storage means for storing a plurality

of images, region information storage means for storing

partial images included in the respective images stored

15 in the image storage means in correspondence with the

respective images, and region feature storage means

for storing features of the partial images stored in

the region information storage means in correspondence

with the partial images, comprising image feature

20 designation means for designating a feature of a search

target image, candidate image determination means for

searching features of partial images in the region

feature storage means on the basis of the feature of

the image which is designated by the image feature

25 designation means, and determining an image which is

made to correspond to a partial image obtained on the

basis of a search result as a candidate image from the

images stored in the image storage means and search result display means for displaying a reduced image of the candidate image determined by the candidate image determination means in a plurality of patterns.

5   In order to achieve the above object, an image search method for an image search apparatus according to the present invention can be connected to an image storage unit which stores a plurality of images, a region information storage unit which stores partial

10   images included in the respective images stored in the image storage unit in correspondence with the respective images, and a region feature storage unit which stores features of the partial images stored in the region information storage unit in correspondence with the partial images, comprising an image feature

15   with the partial images, comprising an image feature designation step of designating a feature of a search target image, a candidate image determination step of searching features of partial images in the region feature storage unit on the basis of the designated

20   feature of the image, and determining an image which is made to correspond to a partial image obtained on the basis of a search result as a candidate image from the images stored in the image storage unit and a search result display step of enlarging the partial image

25   included in the determined candidate image and displaying a reduced image of the candidate image.

      In order to achieve the above object, an image

search method for an image search apparatus according
to the present invention can be connected to an image
storage unit which stores a plurality of images, a
region information storage unit which stores partial
5   images included in the respective images stored in the
image storage unit in correspondence with the
respective images, and a region feature storage unit
which stores features of the partial images in the
region information storage unit in correspondence with
10   the partial images, comprising an image feature
designation step of designating a feature of a search
target image, a candidate image determination step of
searching features of partial images stored in the
region feature storage unit on the basis of the
15   designated feature of the image, and determining an
image which is made to correspond to a plurality of
partial images obtained on the basis of a search result
as a candidate image from the images stored in the
image storage unit and a search result display step of
20   enlarging the plurality of partial images included in
the determined candidate image and displaying a reduced
image of the candidate image.

      In order to achieve the above object, an image
search method for an image search apparatus according
25   to the present invention can be connected to an image
storage unit which stores a plurality of images, a
region information storage unit which stores partial

images included in the respective images stored in the image storage unit in correspondence with the respective images, and a region feature storage unit which stores features of the partial images stored in

5 the region information storage unit in correspondence with the partial images, comprising an image feature designation step of designating a feature of a search target image, a candidate image determination step of searching features of partial images in the region

10 feature storage unit on the basis of the designated feature of the image, and determining an image which is made to correspond to a partial image obtained on the basis of a search result as a candidate image from the images stored in the image storage unit and a search

15 result display step of displaying a reduced image of the determined candidate image in a plurality of patterns.

Other features and advantages of the present invention will be apparent from the following

20 description taken in conjunction with the accompanying drawings, in which like reference characters designate the same or similar parts throughout the figures thereof.

25 BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporates in and constitute a part of the specification,

illustrate embodiments of the invention and, together
with the description, serve to explain the principle of
the invention.

Fig. 1 is a block diagram showing the arrangement
5   of an image search apparatus according to the first
embodiment of the present invention;

Fig. 2 is a block diagram showing the connection
arrangement of various kinds of equipment for realizing
the image search apparatus according to the first
10 embodiment;

Fig. 3 is a conceptual view showing how a control
program and the like are supplied from a CD-ROM 205 to
a computer system;

Fig. 4 is a view for explaining an example of the
15 arrangement of data stored in a ROM 202 in Fig. 2;

Fig. 5 is a view showing the data arrangement of
an image registration program 501, image search program
502, and the like stored in the CD-ROM 205 which is a
portable recording medium;

20 Fig. 6 is a view for explaining an example of the
data arrangement on a RAM 203 at the time of execution
of a processing program;

Fig. 7 is a view showing an example of a search
operation window in a conventional image search system;

25 Fig. 8 is a view showing an example of a still
image registered in an image database;

Fig. 9 is a view showing an example of the data

arrangement of an image database 605 in the first

embodiment;

Fig. 10 is a view showing an example of the data

arrangement of a region database 606;

5   Fig. 11 is a view showing an example of the data

arrangement of a search condition list 607 in the first

embodiment;

Fig. 12 is a view showing an example of the data

arrangement of a region comparison buffer 608 which

10   stores the result obtained by comparing the search

condition designated in step S401 with the regions in

the image extracted in step S402;

Fig. 13 is a view showing an example of the data

arrangement of a search result list;

15   Fig. 14 is a flow chart for explaining an overall

sequence in the image search apparatus according to the

first embodiment;

Fig. 15 is a flow chart for explaining a detailed

processing sequence by an image registration program in

20   the first embodiment;

Fig. 16 is a flow chart for explaining the image

registration program and a region selection processing

sequence in search condition designation processing;

Fig. 17 is a flow chart for explaining in detail

25   the operation of an image search program in step S104

in Fig. 14;

Fig. 18 is a flow chart for explaining in detail

a search condition designation processing sequence in step S401 in the processing by the image search program in Fig. 17;

Fig. 19 is a flow chart for explaining similarity 5 calculation processing in step S404;

Fig. 20 is a flow chart for explaining in detail thumbnail generation processing in step S406;

Fig. 21 is a view showing a window display example on a display 208 which is displayed during 10 image search processing in step S104 in Fig. 14;

Fig. 22 is a view showing a window display example to explain a state wherein an image in a search result display area is selected to perform region selection processing in the image search program;

15 Figs. 23A to 23F are views showing window display examples to explain region selection processing;

Figs. 24A to 24C are views for explaining how an embodiment of thumbnail generation processing is performed;

20 Figs. 25A to 25C are views for explaining how another embodiment of thumbnail generation processing is performed;

Fig. 26 is a view for explaining how thumbnail image generation processing is performed when the areas 25 of a plurality of rectangular regions are made uniform;

Fig. 27 is a view for explaining a thumbnail image generated by thumbnail generation processing; and

Figs. 28A to 28C are views for explaining an embodiment of thumbnail generation processing of generating a plurality of thumbnails with respect to one image.

5

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

An image search apparatus according to an embodiment of the present invention will be described below with reference to the accompanying drawings.

10   <First Embodiment>

An outline of an image search apparatus according to the first embodiment of the present invention will be described first. Fig. 1 is a block diagram showing the arrangement of the image search apparatus according

15   to the first embodiment of the present invention. Referring to Fig. 1, image contents such as still images and moving images as image search targets are stored in an image storage unit 101. Note that each image data is stored in the image storage unit 101,

20   together with a file name corresponding to the image data. The image storage unit 101 is connected to a region information storage unit 102. The region information storage unit 102 stores information indicating a specific region in each image stored in

25   the image storage unit 101. Note that each information indicating a region is stored in the region information storage unit 102 in correspondence with a corresponding

image stored in the image storage unit 101.

The region information storage unit 102 is connected to a region feature storage unit 103. The region feature storage unit 103 stores a feature of

5   each region stored in the region information storage unit 102. Note that a feature of each region is stored in the region feature storage unit 103 in correspondence with information indicating the corresponding region stored in the region information

10   storage unit 102. Such a feature of a region includes, for example, language information such as a keyword representing an object corresponding to the region and image feature information such as the color, shape, or position of the region.

15   An image feature designation unit 104 is used by an operator or the like to designate a feature of an image to be searched out. Features designated by the operator or the like include, for example, language information (e.g., a character string) such as a

20   keyword and image feature information such as the color, shape, or position of a specific region in an image.

A candidate image decision unit 105 is connected to the region feature storage unit 103 and image

25   feature designation unit 104. The candidate image decision unit 105 compares the feature designated by the image feature designation unit 104 with the

features stored in the region feature storage unit 103,

and determines images as candidate images, obtained as

a result of a search, which include regions

corresponding to features identical or similar to the

5   designated feature.

A search result display unit 106 is connected to

the image storage unit 101, region information storage

unit 102, and candidate image decision unit 105. With

regard to the candidate images determined by the

10 candidate image decision unit 105, the search result

display unit 106 displays regions (object regions)

whose features are determined to be identical or

similar to the designated feature or partial images

including the regions in an area with a predetermined

15 size. In displaying a region or a partial image

including the region, the search result display unit

106 displays the region in a larger size than an image

of the region displayed when the entire corresponding

image is displayed in an area with a predetermined

20 size. In addition, in displaying the region or the

partial image including the region, the search result

display unit 106 emphasizes it to allow easy visual

recognition.

The details of the image search apparatus

25 according to this embodiment will be described below.

Fig. 2 is a block diagram showing the connection

arrangement of various kinds of equipment for

implementing the image search apparatus according to
the first embodiment. Referring to Fig. 2, a CPU 201
executes various control operations in this apparatus,
including the processing to be described below, by

5   executing the control programs stored in a ROM 202 or
RAM 203. Fig. 4 is a view for explaining an example of
the arrangement of data stored in the ROM 202 in
Fig. 2. As shown in Fig. 4, a control sequence program
401 is stored in the ROM 202. Fig. 6 is a view for

10 explaining an example of a data arrangement on the RAM
203 at the time of execution of a processing program.
As shown in Fig. 6, the RAM 203 stores an image
registration program 603, image search program 604,
image database 605, region database 606, search

15 condition list 607, region comparison buffer 608, and
search result list 609.

Referring to Fig. 2, a CD-ROM drive 204 reads out
control programs and various kinds of data from a
CD-ROM 205, and provides them for this image search

20 apparatus. Fig. 3 is a conceptual view showing that a
control program and the like are provided from the
CD-ROM 205 to the computer system. Fig. 5 is a view
showing the data arrangement of an image registration
program 501, image search program 502, and the like

25 stored in the CD-ROM 205 which is a portable recording
medium.

When the image registration program 501 and image

- 18 -

search program 502 are loaded from the CD-ROM 205 into

the RAM 203 through the CD-ROM drive 204, the CPU 201

can execute them. That is, the data arrangement on the

RAM 203 shown in Fig. 6 indicates a memory map in a

5   state wherein the image registration program 501 and

image search program 502 stored in the CD-ROM 205 are

loaded into the RAM 203 and can be executed.

In the above program executable state, the image

database 605, region database 606, and the like are

10   loaded and initialized on the memory map by a hard disk

drive 206, in addition to the image registration

program 501 (the image registration program 603 on the

memory map) and the image search program 502 (the image

search program 604 on the memory map).

15   Referring to Fig. 2, the hard disk drive 206

provides a large-capacity storage area in this image

search apparatus. The control programs stored in the

CD-ROM 205 may therefore be installed in the hard disk

drive 206 to be loaded into the RAM 203 as needed. A

20   keyboard 207, display 208, mouse 209, and network card

210 communicatively connect the respective components

described above to each other through a system bus 211.

This image search apparatus can be connected to a

network 212 through the network card 210 and can

25   communicate with other computer equipment 213 connected

to the network 212.

The operation sequence of the image search

apparatus having the above arrangement will be described next. Fig. 14 is a flow chart for explaining the overall operation sequence of the image search apparatus according to this embodiment.

5   First of all, the image registration program 501, image search program 502, and the like stored in the CD-ROM 205 are loaded from the CD-ROM drive 204 into the RAM 203. In addition, the image database 605, region database 606, and the like are loaded from the

10   hard disk drive 206 into the RAM 203. Necessary initialization is then performed (step S101).

     The operator then issues an instruction to cause a branch to the subsequent processing with the keyboard 207 or mouse 209 (step S102). If an instruction for

15   "image registration" is issued as a result of this operation, the flow branches to step S103. If an instruction for "image search" is issued, the flow branches to step S104. If an instruction of other processing is issued, the flow branches to step S105.

20   In step S103, the image registration program 603 is activated to register an image in the image database 605 in Fig. 6. In addition, the information of a region in the registered image is registered in the region database 606. Note that the detail processing

25   sequence in step S103 will be described later with reference to Fig. 15.

     In step S104, the image search program 604 for

the execution of an image search is activated to search
for an image registered in the image database 605 by
referring to the region database 606 in accordance with
operation by the operator. The detailed processing

5   sequence in step S105 will be described in later with
reference to Fig. 17.

Step S105 is the step of performing processing
other than image registration and image search and is
not directly associated with the embodiment of the

10   present invention.

Processing by the image registration program 501
(the image registration program 603 on the memory map)
executed in step S103 will be described. Fig. 15 is a
flow chart for explaining the detailed processing

15   sequence by the image registration program in this
embodiment.

As shown in Fig. 15, first of all, the image
designated by the operator is registered in the image
database 605 (step S201). Fig. 9 is a view showing an

20   example of the data arrangement in the image database
605 in this embodiment. As shown in Fig. 9, "image ID"
for identifying an image, "file name" indicating a file
in which image data is stored, "horizontal size"
indicating the number of pixels of the image in the

25   horizontal direction, and "vertical size" indicating
the number of pixels of the image in the vertical
direction are stored as information associated with

- 21 -

each image (to be referred to as "image information"

hereinafter) in the image database 605 in

correspondence with each other. Assume that the

respective pieces of image information are sorted in

5   ascending order according to the image IDs.

For example, an image with a horizontal size of

1,200, a vertical size of 900, and a file name of

Img100.jpg is stored as an image having an image ID

value of 100 in the image database 605 shown in Fig. 9.

10   In step S201, the operator designates the file

name of an image to be registered. A horizontal size

and vertical size are then obtained from the image data

obtained from the designated file name, and an unused

image ID value is generated as an image ID. These

15   pieces of image information are added to the image

database 605 so as to be sorted in ascending order

according to the image ID. Note that such a processing

sequence is processing generally performed in an image

search apparatus which handles a similar kind of image

20   database, and is known. Therefore, a further detailed

description will be omitted.

Referring to Fig. 15, the processing from step

S202 to step S211 is the processing of registering the

information of a region in the image registered in step

25   S201 into the region database 606. Fig. 10 is a view

showing an example of the data arrangement in the

region database 606. As shown in Fig. 10, "region ID"

- 22 -

for identifying a region, "image ID" for indicating an image to which the region belongs, "region coordinates" representing the location of the region in the image, "parent region" indicating a parent region to which a

5   target region belongs, "keyword" expressing the contents of the region by a character string, and "color feature amount" representing the color feature of the region are stored as information associated with each region (to be referred to as "region information"

10   hereinafter) in the region database 606. Assume that the respective pieces of region information are sorted in ascending order according to the region IDs.

In this embodiment, as "region ID", the value obtained by combining a three-digit value, set as three

15   low-order digits, for identifying a region in the same image and the image ID value of the image to which the region belongs as upper-order digits is used. This allows pieces of region information associated with the same image to be complied into one group in the region

20   database 606, as shown in Fig. 10. Note that the number of digits of an image ID may be other than three.

In addition, "region coordinates" express a target region, which is regarded as a polygon, by a

25   list of the coordinates of the vertexes of the polygon. Each coordinate pair is expressed by a coordinate system in which an upper left point of a target image

is set as an origin, and the x- and y-coordinate axes are respectively set in the rightward and downward directions. For example, the region coordinates of a partial image 803 corresponding to "car" are given as

5 ((780, 720), (780, 780),...) as region information corresponding to the region ID "100001" in Fig. 10. In this case, the coordinates of a vertex 804 of the partial image 803 shown in Fig. 8 are (780, 720), and the coordinates of a vertex 805 correspond to (780,

10 780).

In some image, since a person stands in front of a dog, the region of the dog is divided into two regions. In order to cope with a case wherein a region which should be a single region is divided by another

15 region, a plurality of regions can be stored in "region coordinates" in this embodiment. For example, as shown in Fig. 10, ((300, 420),...),((240, 360),...) are set in the region coordinate field corresponding to the region ID "101001". This indicates that this region is

20 constituted by two regions, i.e., the region expressed by ((300, 420),...) and the region expressed by ((240, 360),....)

"Parent region" shown in Fig. 10 indicates the parent/child relationship or inclusive relationship

25 between regions. For example, the region of a partial image 802 corresponding to "house" is constituted by the two regions of a partial image 806 corresponding to

"roof" and "wall" and a partial image 807 corresponding
to "window". The region of the partial image 807
corresponding to "window" is included in the region of
the partial image 806 corresponding to "roof" and

5   "wall". In other words, the parent region of the
region of the partial image 807 corresponding to
"window" is the region of the partial image 806
corresponding to "roof" and "wall". The parent region
of the region of the partial image 806 corresponding to

10   "roof" and "wall" is the partial image 802
corresponding to the "house".

In the region database 606 shown in Fig. 10,
these relationships are shown in "parent region". For
example, in the parent region field of the partial

15   image 807 corresponding to "window" indicated by the
region ID "100006", the region ID "100005"
corresponding to "wall" of the partial image 806 is
stored. In the parent region field of the region
corresponding to the partial image 806 in which "wall"

20   indicated by the region ID "100005" is included, the
region ID "100002" corresponding to the partial image
802 corresponding to "house" is stored. Note that
since there is no parent region of the partial image
802 corresponding to "house", the invalid value "-1" is

25   stored as a region ID in the parent region field
corresponding to the region ID "100002".

A character string such as a keyword which

expresses the contents of a target region is stored in "keyword". Such a character string need not be formed by one word, and a keyword can be expressed by a natural sentence. A plurality of contents can be

5   stored in "keyword". In this case, the contents can be separated by delimiting character strings expressing the contents with ",".

As the color feature amount of the region indicated by "region coordinates", a color histogram is

10   stored in "color feature amount". A color histogram can be obtained by totalizing the colors of the respective pixels contained in the region indicated by "region coordinates" in the quantum box obtained as a result of uniformly quantizing an RGB color space with

15   three bits for each color, and normalizing the resultant data such that the sum of histogram frequencies become 1,000. The values of the respective quantum boxes of histograms obtained as a result of this processing are so stored in "color feature amount"

20   so as to be delimited with "," and arranged in a predetermined order.

A sequence for registering a region in the image, which has been registered in step S201, in the region database 606 described above will be descried below

25   with reference to steps S202 to S211.

First of all, a region to be registered in the region database 606 is set (step S202). In this region

setting processing, the image registered in step S201
is displayed in a window in the display 208, and the
operator designates the vertexes of a polygon by
pointing the vertexes of the regions to be registered

5   with the mouse cursor using the mouse 209 and clicking
the vertexes one by one. Finally, by clicking the
vertex designated at first, a polygonal region defined
by connecting the designated vertexes with straight
lines can be set. When a plurality of regions are to

10 be designated, another polygonal region can be set by
performing the same operation as described above. The
list of set coordinates coincides with the contents
stored in "region coordinates" of the region
information in Fig. 10. When the operator finishes

15 setting the region to be registered, the flow advances
to step S203 in accordance with a setting end
instruction by the operator.

        Step S203 is the processing of setting a content
to be stored in "keyword" with respect to the region

20 set in step S202. This keyword setting processing is
performed by inputting a character string stored in
"keyword" from the keyboard 207. If there are a
plurality of contents to be set, they can be input
while being delimited with "," input from the keyboard

25 207. When the setting is complete, the flow advances
to step S204 in accordance with a setting end
instruction from the operator.

Step S204 is the feature amount setting processing of setting a content to be stored in "color feature amount" of the region information with respect to the region set in step S202. The manner of
5   obtaining a content to be stored in "color feature amount" is the same as that described in the description of the region database 606 with reference to Fig. 10. This content can be automatically obtained without the mediacy of the operator. When this feature
10   amount setting processing is complete, the flow advances to step S205.

In step S205, a branch occurs to the subsequent processing depending on whether any parent region exists with respect to the region set in step S202. If
15   the operator determines that there is no parent region (No), the flow advances to step S206. If the operator determines that there is a parent region (Yes), the flow advances to step S207. In general, in the initial stage of registration of a region, no parent region has
20   often not been registered. In such a case, the flow advances to step S206. If a parent region has already been registered, the flow advances to step S207. In order to use such a region registration method, therefore, a parent region must be registered before
25   child regions.

Step S206 is the processing to be performed when no parent region exists. In this processing, "-1" is

set as a value of "parent region" of the region
information, as shown in Fig. 10. When the processing
is complete, the flow advances to step S210.

In step S207, a region selection window for the
5   selection of a region is displayed on the display 208
to allow selection of a parent region in step S208. In
this region selection window, the image registered in
step S201 is displayed. When the processing is
complete, the flow advances to step S208.

10   Step S208 is the region selection processing of
selecting a region serving as a parent region which has
already been registered in the region database 606.
The region ID of the parent region can be obtained from
the region information of the selected parent region.
15   The details of the region selection processing will be
described later with reference to Fig. 16. When the
processing is complete, the flow advances to step S209.

In step S209, the region ID of the parent region
obtained in step S208 is set as a value of "parent
20   region" of the region information. When the processing
is complete, the flow advances to step S210.

Step S210 is the processing of registering the
set region in the region database 606 on the basis of
the region information set in steps S202 to S209. With
25   the processing from step S202 to step S209, the region
information constituted by "region coordinates",
"keyword", "color feature amount", and "parent region"

is set. In this case, as "image ID" of the region

information, the image ID value obtained when the image

was registered in the image database 605 in step S201

is used. A value other than the region ID of the

5   region information which is registered in the region

database 606 is generated by using this image ID and

set as "region ID". The obtained region information is

registered such that the region ID values are sorted in

ascending order in the region database 606, as shown in

10   Fig. 10. When the processing in step S210 is complete,

the flow advances to step S211.

In step S211, a branch occurs to the subsequent

processing depending on whether a region is to be

continuously registered. If a region is to be

15   continuously registered (No), the flow returns to step

S202 to perform the above processing. If region

registration is to be ended (Yes), the image

registration program is terminated.

"Region selection processing" performed in step

20   S208 in Fig. 15 and in step S504 in Fig. 18 (to be

described later) will be described in detail next with

reference to Figs. 16 and 23A to 23F. Assume that the

region database is in the state shown in Fig. 10.

Fig. 16 is a flow chart for explaining a sequence for

25   region selection processing in the image registration

program and search condition designation processing.

Figs. 23A to 23F are views each showing a window

display example to explain region selection processing.

In the region selection processing, a region is selected by using the mouse 209 in a region selection window 2300 like the one shown in Fig. 23A. The region selection window 2300 shown in Fig. 23A displays an image 2301 as a region selection target. In this case, the region selection window 2300 in step S208 in the flow chart shown in Fig. 15 is the window displayed in step S207, and the region selection window 2300 in step S504 is the window emphasized in step S503.

First of all, by storing the region ID of the selected region in the region database 606 shown in Fig. 6, "-1" is stored as an initial value in "selected region" indicating the selected region (step S301). If "-1" is stored in "selected region", it is regarded that the entire image is selected.

The display in the region selection window 2300 is then updated (step S302). If, for example, the region 802 of "house" in Fig. 8 is selected, the contour of the selected region is indicated by thick lines as indicated by reference numeral 2303 in Fig. 23B to allow a visual check on the region indicated by "selected region". According to another method, as indicated by reference numeral 2311 in Fig. 23F, the selected region is displayed in a normal way, while the regions other than the selected region can be displayed in a display form different from that

for the selected region. For example, in such regions, the pixels of an image to be displayed are decimated by replacing alternate dots with black dots.

The contour of a selected region or the boundary

5   between a selected region and an unselected region can be easily obtained by connecting the coordinates the region in "region coordinates" in the region database 606 with straight lines in the case of the region selection in step S208, or by connecting the

10   coordinates of the region in "region coordinates" in the search result list 609 in the case of the region selection in step S504. If "-1" is stored in "selected region", since it indicates that the entire image is selected, the outer frame of the image is displayed by

15   thick lines, as indicated by reference numeral 2301 in Fig. 23A.

In step S303, a branch occurs to the subsequent processing depending on whether one point pointed by the mouse cursor in the selection region window is

20   clicked with the mouse 209. If the point is clicked (Yes), the flow advances to step S304. If the point is not clicked (No), the flow advances to step S316.

In step S304, a branch further occurs to the subsequent processing depending on whether the clicked

25   position pointed by the mouse cursor is inside the image indicated by reference numeral 2301 in Fig. 23A in the region selection window. If the position

pointed by the mouse cursor is inside the image (Yes),
the flow advances to step S305. If the position
pointed by the mouse cursor is outside the image (No)
indicated by reference numeral 2312 in Fig. 23F, the

5   flow returns to step S301 to shift the entire image to
the selected state. If a position outside the image is
selected in the state shown in Fig. 23B, the state
shown in Fig. 23A is set through the processing in
steps S301 and S302.

10   In step S305, a branch occurs to the subsequent
processing depending on the value of "selected region".
If the value of "selected region" is -1 (Yes), it is
determined that the entire image is selected, and the
flow advances to step S306. If the value of "selected

15   region" is not -1 (No), it is determined that a
specific region is selected, and the flow advances to
step S309.

     In step S306, the image 2301 as a region
selection target is searched for a region which

20   includes the position clicked in step S303 and has no
parent region. In the region selection processing in
step S208, the image ID of the image serving as a
search range is the image ID of the image registered in
step S201. In the region selection processing in step

25   S504, this image ID is the image ID of the image
emphasized in step S503. The image ID of the image
emphasized in step S503 can be obtained from the search

result list 609 described later. The region database

606 is then searched for the region ID of a region

which has this image ID and the polygonal region stored

in "region coordinates" including the clicked position

5   (coordinates) and has -1 as the value of "parent

region".

In this case, whether "region coordinates"

corresponding to the region ID include the clicked

position (coordinates) can be checked by searching the

10   region database 606 and using "region coordinates" in

the case of the region selection processing in step

S208 or when the entire image is displayed by a

switching button 2110 in step S503. If the thumbnail

images generated in step S406 are displayed in step

15   S503, the above decision can be made by searching the

search result list 609 and using "region coordinates",

and a corresponding region ID can be obtained.

In step S307, a branch occurs to the subsequent

processing depending on whether a region for which a

20   search was made in step S306 is found. If such a

region is found (Yes), the flow advances to step S308.

If no such region is found (No), the flow returns to

step S302.

In step S308, the region ID value corresponding

25   to the region found in step S306 is stored in "selected

region" to set a child region. When the processing is

complete, the flow advances to step S302.

If, for example, the position indicated by
reference numeral 2302 is clicked in the state shown in
Fig. 23A after the processing in step S302, the flow
advances to step S306 through the processing in steps
5   S304 and S305. In step S306, when the region database
606 shown in Fig. 10 is searched, the house
corresponding to the region ID "100002" is selected
instead of the roof corresponding to the region ID
"100004". The state shown in Fig. 23B is then set
10   through steps S307, S308, and S302. Consequently, as
indicated by reference numeral 2303, the contour of the
house is displayed by thick lines.

In step S309, a branch occurs to the subsequent
processing depending on whether the position
15   (coordinates) pointed by the clicked mouse cursor is
included in the region corresponding to the region ID
stored in "selected region". Whether the position
(coordinates) pointed by the clicked mouse cursor is
included in the region corresponding to the region ID
20   stored in "selected region" can be easily determined by
comparing the corresponding coordinates with the
coordinates of the polygon stored in "region
coordinates" in the region database 606 which
corresponds to this region ID in the case of the region
25   selection processing in step S208 or when the entire
image is displayed by the switching button 2110 in step
S503.

If the thumbnail images generated in step S406 are displayed in step S503, the above decision can be easily made by comparing the corresponding coordinates with the coordinates of the polygon corresponding to

5   the target region ID stored in "region coordinate" in the search result list 609. If the position is included in the selected region (Yes), the flow advances to step S310. If the position is not included in the selected region (No), the flow advances to step

10   S313.

In step S310, the region database 606 is searched for a child region of the region which includes the position clicked in step S303 and corresponds to the region ID stored in "selected region". The region

15   information as a search range is region information having a region ID in "parent region" which is identical to "selected region". The region information in the region database 606 is then searched for region information having a polygonal region which includes

20   the clicked position (coordinates) and is stored in "region coordinates".

If the thumbnail images generated in step S406 are displayed in step S503, the coordinates clicked in step S303 are converted into coordinates on the image

25   stored in the image database 605 from the relationship between the coordinates of the polygon in "region coordinates" in the search result list 609 which

- 36 -

correspond to the region ID stored in "selected region"
and "region coordinates" in the region database 606
which correspond to this region ID before it is
determined whether the clicked position (coordinates)

5   is included. Whether the clicked position
(coordinates) is included can be easily determined by
comparing the clicked coordinates with the coordinates
of the polygon which are stored in "region coordinates"
in the region database 606.

10   In step S311, a branch occurs to the subsequent
processing depending on whether region information for
which a search was made in step S310 is found. If such
region information is found (Yes), the flow advances to
step S312. If no such region information is found

15 (No), the flow advances to step S302.

       In step S312, the value of "region ID" of the
region information of a child region of "selected
region" found in step S310 is stored in "selected
region". When this processing is complete, the flow

20 returns to step S302.

       If, for example, the position indicated by
reference numeral 2304 is clicked in the state shown in
Fig. 23B after step S302, the flow advances to step
S310 through steps S303, S304, S305, and S309. In step

25 S310, as a result of searching the region database 606
shown in Fig. 10, the wall corresponding to the region
ID "100005" is selected instead of the window

corresponding to the region ID "100006". In addition, the state shown in Fig. 23C is set through steps S311, S312, and S302, and the contour of the wall is displayed by thick lines, as indicated by reference
5   numeral 2305.

In step S313, a search is made for a parent region including the position clicked in step S303 by tracing the parent region of the region corresponding to the region ID stored in "selected region". When the
10 thumbnail images generated in step S406 are displayed before the search, the coordinates clicked in step S303 are converted into coordinates on the image stored in the image database 605 from the relationship between the coordinates of the polygon in "region coordinates"
15 in the search result list 609 which correspond to the region ID stored in "selected region" and "region coordinates" of this region ID in the region database 606.

Subsequently, "parent region" of the region
20 information having a region ID identical to the value stored in "selected region" is set as a target parent region in the region database 606, and it is determined whether the polygonal region stored in "region coordinates" of the region information which has this
25 region ID value as "region ID" includes the clicked coordinates. If the coordinates are not included in the target parent region, and the target parent region

further has a parent region, i.e., "parent region) of the region information of the target parent region is not "-1", "parent region" of the region information of the target parent region is set as a target parent

5   region, and a search is made for a parent region including clicked coordinates until there is no parent region.

In step S314, a branch occurs to the subsequent processing depending on the result of the search in

10   step S313. If a parent region including the clicked position is found (Yes), the flow advances to step S315. If no parent region is found (No), the flow advances to step S306.

If the position indicated by reference numeral

15   2309 is clicked in the state shown in Fig. 23D after step S302, the flow advances to step S313 through steps S303, S304, S305, and S309. If it is determined in step S313 that no parent region is found, the flow advances to step S306 through step S314. In step S306,

20   as a result of searching the region database 606 shown in Fig. 10, the tree corresponding to the region ID "100003" is selected. Thereafter, the state shown in Fig. 23E is set through steps S311, S312, and S302. As indicated by reference numeral 2310, the contour of the

25   tree is displayed by thick lines.

In step S315, the value of "region ID" of the region information of the parent region found in step

S313 is set in "selected region". When the processing
is complete, the flow advances to step S302.

If, for example, the position indicated by
reference numeral 2308 is clicked in the state shown in
5   Fig. 23D after step S302, the flow advances to step
S313 through steps S303, S304, S305, and S309. In step
S313, the house corresponding to the region ID "100002"
is searched out as a parent region. The state shown in
Fig. 23B is set through steps S314, S315, and S302, and
10   the contour of the house is displayed by thick lines,
as indicated by reference numeral 2303.

In step S316, a branch occurs to the subsequent
processing depending on whether the mouse cursor is
placed on the region corresponding to "selected
15   region", and the region corresponding "selected region"
is dragged outside the region selection window. If the
region is dragged (Yes), the region selection
processing is terminated. Otherwise (No), the flow
advances to step S317.

20   In step S317, a branch occurs to the subsequent
processing depending on whether the region selection
processing is terminated in accordance with an
instruction from the operator. If the region selection
processing is to be continued (No), the flow returns to
25   step S303. If an instruction to terminate the region
selection processing is issued (Yes), the region
selection processing is terminated.

Image search processing by an image search
program (the image search program 502 in Fig. 5 or the
image search program 604 in Fig. 6) in step S104 in
Fig. 14 will be described next.

5   Fig. 21 is a view showing a window display
example on the display 208 during the image search
processing in step S104 in Fig. 14. Referring to
Fig. 21, the area denoted by reference numeral 2102 is
a search instruction area for various instructions for

10 a search, and the area denoted by reference numeral
2103 is a search result display area for displaying a
search result.

The following are displayed in the search
instruction area 2102: an image condition area 2104 for

15 setting a feature of a desired image; a keyword area
2106 for setting a keyword for the desired image; a
handwriting button 2105 which issues an instruction to
input a feature of the image by handwriting; a search
button 2107 which issues an instruction to search for

20 an image which satisfies the conditions input in the
image condition area 2104 and keyword area 2106; and
the switching button 2110 for switching the display
forms of search results to be displayed in the search
result display area 2103.

25   In the search result display area 2103, a list of
thumbnails of the images obtained as a result of a
search is displayed as indicated by reference numerals

- 41 -

2008 and 2009. Note that the thumbnail images 2008 and 2009 are thumbnails of the images obtained as a result of the search.

Fig. 17 is a flow chart for explaining in detail the operation of the image search program in step S104 in Fig. 14. First of all, search condition setting processing is performed to set a condition for a search for a desired image (step S401). With this processing, the search condition list 607 shown in Fig. 6 is generated. The details of this search condition setting processing and search condition list 607 will be described later with reference to Figs. 18 and 11.

Images to be compared with the search condition set in step S401 are extracted from the image database 605 one by one (step S402). More specifically, the values in "image ID" are sequentially extracted one by one from the start of the image database 605. If a target image can be extracted (No in step S403), the flow advances to step S404. If all images are extracted (Yes in step S403), the flow advances to step S408 through step S403.

Step S404 is similarity calculation processing of calculating the similarity between each image extracted in step S402 and the search condition set in step S401. With this processing, the region database 606 is referred to on the basis of the image ID extracted in step S402, and computation is performed by collating

with the search condition list 607 to generate the

region comparison buffer 608, thereby obtaining the

similarity with the image extracted in step S402. Note

that processing associated with this similarity

5   calculation will be described in detail later with

reference to Fig. 19.

        In step S405, a branch occurs to the subsequent

processing depending on whether the similarity obtained

in step S404 is higher than a predetermined threshold.

10   If the similarity is higher than the predetermined

threshold (Yes), it is determined that the image

extracted in step S402 satisfies the search condition

set in step S401, and the flow advances to step S406.

If the similarity is lower than the predetermined

15   threshold (No), it is determined that the image

extracted in step S402 has not satisfied the search

condition set in step S401, and the flow advances to

step S402.

        In step S406, thumbnail generation processing of

20   generating thumbnail images of the images obtained as a

search result which are displayed in the search result

display area 2103 is performed. In this processing,

thumbnail images are generated by using the image

database 605, region database 606, and region

25   comparison buffer 608, and "region coordinates" for

representing each region in the thumbnail image

corresponding to each condition in the search condition

list 607 are obtained. This processing will be described in detail later with reference to Fig. 20.

Step S407 is the processing of adding information about the image which satisfies the condition set in
5   step S401 to the search result list 609. Fig. 13 is a view showing an example of the data arrangement of the search result list. As shown in Fig. 13, the information about the image which satisfies the condition set in control sequence program 401 (to be
10   referred to as "search result information" hereinafter) is constituted by "image ID", "region ID", "condition number", "thumbnail image", "region coordinates", and "similarity".

First of all, "image ID" is the image ID of the
15   image extracted in step S402. "Region ID" is a region ID in the region database 606 which corresponds to a region in the image which satisfies each condition in the search condition list 607, and can be obtained from the region ID which is generated in step S404 and
20   stored in the region comparison buffer 608. If a plurality of region IDs are present, they are basically delimited with "," and stored in the order in which they are stored in the region comparison buffer 608. If a plurality of identical regions are present in the
25   region comparison buffer 608, only one region is stored, and a condition number which exhibits the highest individual condition similarity is selected as

- 44 -

a condition number corresponding to the region.

In addition, the number of a condition which "region ID" satisfies is stored in "condition number", and can be obtained from the region comparison buffer
5   608. The file name of the thumbnail image generated in step S406 is stored in "thumbnail image". In addition, the coordinates of the vertexes of a polygon representing the region stored in "region ID" in the thumbnail image generated in step S406 are stored in
10   "region coordinates".

An expression for one region in "region coordinates" is the same for region coordinates in the region database 606. Since regions corresponding to a plurality of region IDs are stored in "region
15   coordinates" in the search result list 609, information about the regions corresponding to the respective region IDs is delimited with "," and stored, and the delimited pieces of information are stored in the same order as the region IDs stored in "region ID". The
20   similarity obtained in step S404 is stored in "similarity". In step S407, these pieces of search result information are added to the end of the search result list 609. When the above processing is complete, the flow advances to step S402.

25   Step S408 is the processing of displaying a search result on the display 208. Images indicated by "thumbnail image" are sequentially displayed from the

start of the search result list 609 from the upper left
to the right in the search result display area 2103 in
Fig. 21. In addition, the color of the keyword
displayed in the keyword area 2106 in the search
5   instruction area 2102 is changed. As will be described
later, in thumbnail generation processing in step S406,
the contours of the respective regions satisfying the
respective conditions in the search condition list 607
generated in step S401 are edged with thick lines in
10   different colors determined for the respective
condition numbers. In the thumbnail image denoted by
reference numeral 2109 in Fig. 21, regions are
expressed by "contour emphasis with dots", "no contour
emphasis", and "contour emphasis with thick lines"
15   instead of colors. Such an expression can also be
used.

In the same manner as described above, the
characters of keywords are displayed in the keyword
area 2106 in colors determined for the respective
20   condition numbers. Alternatively, the character
strings of the keywords may be edged with thick lines
in different colors determined for the respective
condition numbers. In addition, the colors of the
thick lines with which the respective regions displayed
25   in the image condition area 2104 in the search
instruction area 2102 are edged are changed or such
colors are added. As in the case of keywords, the

respective regions displayed in the image condition

area 2104 are edged with thick lines in colors

determined for the respective condition numbers.

As will be described later, some region displayed

5   in the image condition area 2104 may have already been

edged with thick lines in a specific color. In this

case, the color of the edging thick lines is changed.

Otherwise, edging thick lines are added. This makes it

possible to easily grasp the correspondence between a

10   condition as a feature of each image, a condition as a

keyword, and a condition with which a region in a

search result satisfies. The user can therefore easily

check the search result. When the processing is

complete, the flow advances to step S409.

15   Step S409 is the processing of switching displays

for a check on a search result. When the switching

button 2110 in Fig. 21 is clicked with the mouse 209,

the thumbnails displayed in the search result display

area 2103 can be switched from the images represented

20   by "thumbnail image" in the search result list 609 to

the reduced images of the images indicated by "file

name" in the image database 605. When the switching

button 2110 is clicked again, the thumbnails displayed

in the search result display area 2103 are returned to

25   the images represented by "thumbnail image" in the

search result list 609.

Subsequently, the thick lines of the region

- 47 -

corresponding to condition number 1 in the region
comparison buffer 608 are blinked. In addition, the
thick lines of a region in the image condition area
2104 which corresponds to condition number 1 in the
5   search condition list 607 are blinked in the search
instruction area 2102, and the character string of a
keyword in the keyword area 2106 is blinked. In this
case, "condition number" is a number for identifying
each condition information. Serious numbers are set in
10   this field with 1 being assigned to the condition
number of the first condition information in the search
condition list 607. The search condition list 607 will
be described later.

When the switching button 2110 is repeatedly
15   clicked, similar processing is repeated in the order of
condition number 2, condition number 3,... in the
search condition list 607, thereby switching regions
and keywords corresponding to blinking conditions.
When the processing for all search results in the
20   search condition list 607 is complete, the state before
the first clicking of the switching button 2110, i.e.,
the state immediately after the completion of the
processing in step S408, is restored. Note that target
thick lines to be blinked can be easily obtained by
25   using "region coordinates" in the search result list
609 and search condition list 607.

When the switching button 2110 is not to be

clicked, a keyword displayed in the keyword area 2106
or a region displayed in the image condition area 2104
is clicked with the mouse 209. With this operation, a
target keyword character string is obtained from the

5   coordinates pointed by the clicked mouse cursor or a
target region is obtained by searching the search
condition list 607, and a corresponding condition
number is obtained, thereby blinking the thick lines of
the region in the image condition area 2104 which

10 corresponds to the condition number and the character
string of the keyword in the keyword area 2106. In
addition, thick lines corresponding to a region in the
region comparison buffer 608 which corresponds to the
condition number in the thumbnail displayed in the

15 search result display area 2103 are blinked.

In step S410, a branch occurs to the execution of
the end of the processing in accordance with an
instruction from the operator. That is, when an end
button 2112 is clicked with the mouse 209 (Yes), it is

20 determined that an instruction to end the image search
processing is issued, and the image search processing
is terminated. If a clear button 2111 is clicked (No),
it is determined that an image search is to be
performed again. In this case, the display in the

25 image condition area 2104 and the display in the
keyword area 2106 are cleared, and the search condition
list 607 is initialized. The flow then advances to

step S401.

The search condition designation processing in step S401 will be described with reference to Figs. 11 and 18. By this search condition designation
5 processing, search conditions for searching for an image are stored in the search condition list 607.

Fig. 11 is a view showing an example of the data arrangement of the search condition list 607 in this embodiment. Referring to Fig. 11, each row indicates
10 the respective conditions for searching for a desired image. Information on each row which is associated with each condition will be referred to as "condition information" hereinafter. Each condition information in this embodiment is constituted by "condition
15 number", "region coordinates", "keyword", "color feature amount", and "parent region", as shown in Fig. 11.

First of all, "condition number" is a number for identifying each condition information. In this field,
20 serial numbers are set with 1 being assigned to the condition number of the first condition information in the search condition list 607. When a partial image as a search condition, i.e., a region, is input in the image condition area 2104, "region coordinates" express
25 the region by the vertexes of a polygon. A list of the coordinates of the vertexes is stored in this field. This expression method is the same as that for region

coordinates in the region database 606. If no image as
a search condition is designated as in condition
information corresponding to condition number 1 in
Fig. 11, no information is stored in "region
5 coordinates".

When words such as keywords which express
contents as search conditions are input in the keyword
area 2106, the character strings of these words are
stored in "keyword". These character strings need not
10 be formed by one word, and may be expressed by a
natural sentence. A plurality of contents can be
stored in "keyword". In this case, the contents can be
separated by delimiting the character strings
expressing the contents with ",". If no keyword as a
15 search condition is designated as in condition
information corresponding to condition number 3 in
Fig. 11, no information is stored in "keyword".

When a partial image as a search condition, i.e.,
a region, is input in the image condition area 2104,
20 the color feature amount of the region is stored in
"color feature amount". The expression method for this
is the same as that for the color feature amounts in
the region database 606. If no image as a search
condition is designated as in condition information
25 corresponding to condition number 1 in Fig. 11, no
information is stored in "color feature amount".

In addition, the value which is valid when region

information in a thumbnail displayed in the search

result display area 2103 is copied to the image

condition area 2104 is stored in "parent region". As

will be described later, if a region to be copied has

5   child regions in the region database 606, the pieces of

information of these regions are also copied by tracing

back the descendant regions. In such a case,

"condition number" of parent search information is

stored in "parent region" of search information having

10   a parent region. The invalid value "-1" is stored in

"parent region" of condition information having no

parent region.

        Fig. 18 is a flow chart for explaining in detail

a sequence for search condition designation processing

15   in step S401 in the processing by the image search

program in Fig. 17. First of all, a branch occurs to

the subsequent processing in accordance with operation

by the operator (step S501). If the handwriting button

2105 in Fig. 21 is clicked with the mouse 209, the flow

20   advances to step S502. If a thumbnail image displayed

in the search result display area 2103 is clicked with

the mouse 209, the flow advances to step S503. If the

image condition area 2104 is clicked with the mouse

209, the flow advances to step S506. If the keyword

25   area 2106 is clicked with the mouse 209, the flow

advances to step S508. If the search button 2107 is

clicked with the mouse 209, the search condition

designation processing is terminated.

Step S502 is the processing to be performed when the handwriting button 2105 is clicked with the mouse 209. A partial image such as a graphic pattern as a

5 search condition is input to the image condition area 2104 by handwriting inputting with the mouse 209. Then, "region coordinates" are extracted from the input partial image, i.e., the input region. In addition, "color feature amount" of this region is extracted. A

10 technique about inputting of a graphic pattern with the mouse is processing which is generally performed and known, e.g., a drawing application in Microsoft Word 2000, and hence a detailed description thereof will be omitted.

15 In this case, with regard to "region coordinates" of the input region, by obtaining a polygon circumscribed to the input region, the vertexes of the polygon can be obtained. In addition, "feature amount" of the region is obtained by the same method as the

20 method described above. "Region coordinates" and "color feature amount" obtained in this manner are added immediately after the valid condition information stored in the search condition list 607. With this operation, "condition number" is also automatically

25 calculated. As a result, "keyword" is cleared, and "-1" is stored in "parent region". When the processing is complete, the flow advances to step S501. In the

state after step S502, for example, condition information like that corresponding to condition number 3 in Fig. 11 is set.

Step S503 is the processing to be performed when a thumbnail displayed in the search result display area 2103 is clicked with the mouse 209. When a thumbnail is clicked, the region where the clicked thumbnail is emphasized by being displayed is edged with thick lines. If a region in a thumbnail displayed in the search result display area 2103 is edged with thick lines, the thick lines are removed.

If, for example, the thumbnail 2109 in Fig. 21 is clicked, a thumbnail denoted by reference numeral 2201 in the search result display area 2103 shown in Fig. 22 is displayed. Fig. 22 is a view showing a window display example to explain a state wherein an image in the search result display area is selected to perform region selection processing by the image search program. When the processing is complete, the flow advances to step S504.

Step S504 is region selection processing of selecting a region from the thumbnail image emphasized in step S503. The details of this processing have been described with reference to Fig. 16. In the processing, a region is selected, and the selected region is dragged by using the mouse 209 and dropped at a predetermined position in the image condition area

2104. With this operation, the flow advances to step S505.

In step S505, the region selected in step S504 and its descendant regions are displayed at the
5   position in the image condition area 2104 at which the regions are dropped. Step S505 is the processing of adding search conditions to the search condition list 607 on the basis of pieces of information about the region selected in step S504 and all descendant regions
10 of the selected region.

If the region ID of the region selected in step S504 does not exist in the search result list 609, the region ID of a parent region existing in the search result list 609 is obtained by tracing back "parent
15 region" in the image database 605. The reduction ratio between a polygonal region in the search result list 609 and a polygonal region in the region database 606 can be obtained from the relationship between the coordinates of a polygon which are stored in "region
20 coordinates" in the search result list 609 and correspond to this region ID or the region ID of the region selected in step S504 and the coordinates of a polygon in "region coordinates" in the region database 606.

25 The coordinates of the polygons of the region selected in step S504 and its descendant regions are converted into reduced coordinates. In addition, the

movement amount of the region can be obtained from the relationship between the coordinates of the polygon at the position in the image condition area 2104 at which the region selected in step S504 is dropped and the

5 coordinates of the reduced polygon obtained in the above manner. The reduced coordinates of the polygons of the region selected in step S504 and its descendant regions are shifted to coordinates in the image condition area 2104. The reduced region coordinates

10 obtained in this manner are sequentially added as individual conditions to "region coordinates" in the search condition list 607, starting from the region selected in step S504.

"Keyword" and "color feature amount" in the

15 search condition list 607 are copied as "keyword" and "color feature amount" corresponding to each region in the region database 606. With respect to the region selected in step S504, "-1" is stored in "parent region" in the search condition list 607. With respect

20 to the remaining regions, values are so stored as to maintain the same parent/child relationship by referring to "parent region" in the region database 606 and using "condition number" in the search condition list 607.

25 Assume that in the state shown in Fig. 23C, a wall 2305 is dragged and dropped into the image condition area 2104. In this case, as indicated by

condition numbers 4 and 5 in the search condition list 607 in Fig. 11, the information of the wall region is registered as a condition together with the wall region. If the entire image is selected in step S504,

5   the information of all the regions included in the selected image is added to the search condition list 607 in step S505.

After the search information is added to the search condition list 607, the region selected in step

10   S504 is displayed at the position in the image condition area 2104 at which the region is dropped. In addition, the character strings of the currently added search conditions which are stored in "keyword" are displayed. In this case, the respective search

15   conditions are displayed with line feeds. When the processing is complete, the flow advances to step S501.

Step S506 is the processing to be performed when the image condition area 2104 is clicked with the mouse 209. That is, in this processing, a region displayed

20   in the image condition area 2104 is selected with the mouse 209. In this case, a region is selected in the same manner as in step S208 by referring to "condition number", "region coordinates", and "parent region" in the search condition list 607. In this case, a

25   parent/child relationship is grasped by using condition numbers instead of region IDs. In the image condition area 2104, a selected region is displayed with its

contour being edged with thick lines as in step S208. If there is a keyword corresponding to the selected region in the search condition list 607, the keyword displayed in the keyword area 2106 is displayed in a

5   color different from those of the remaining keywords. When the processing is complete, the flow advances to step S507.

Step S507 is the processing of changing the size, position, and color of the region selected in step

10 S506, as needed. Changing the size, position, and color of a graphic pattern (region) with the mouse is processing generally performed in a drawing application in Microsoft Word 2000 or the like and is known. A detailed description of this processing will therefore

15 be omitted. In accordance with such changes, the values of "region coordinates" and "color feature amount" in the search condition list 607 are changed. If the selected region has child regions, similar changes are made by tracing back the descendant

20 regions. When the processing is complete, the flow advances to step S501.

Step S508 is the processing to be performed when the keyword area 2106 is clicked. In this step, a keyword is input or edited. Assume no information is

25 input to the image condition area 2104, no region is selected in the image condition area 2104, or the entire image condition area 2104 is selected. In this

case, a keyword can be input regardless of the regions in the image condition area 2104. If the character strings displayed in the keyword area 2106 are present, the character strings are displayed in black. In

5 addition, a new line is started at the line of the last character string displayed in the keyword area 2106, and the cursor is displayed at the start of the new last line.

When a keyword is input from the keyboard 207,

10 the input character string is displayed in red. If a place other than keyword area 2106 is clicked with the mouse 209, the keyword input operation is terminated, and the keyword newly input in red is stored in the search condition list 607. For example, as indicated

15 by condition number 1 in Fig. 11, "region coordinates" and "color feature amount" are cleared, and "-1" is stored in "parent region". If a region in the image condition area 2104 has been selected and a character string has been stored in "keyword" in the search

20 condition list 607 which corresponds to the region, the corresponding character string in the keyword area 2106 is displayed in red, and the remaining character strings are displayed in black, thereby allowing the operator to identify them. The cursor is displayed at

25 the start of these character strings to allow the operator to edit the character strings and input a new keyword. A newly input character string is displayed

in, for example, red.

If a region has been selected in the image condition area 2104 and no character string corresponding to the region is stored in "keyword", the
5   character strings displayed in the keyword area 2106 are displayed in black. In addition, a new line is started at the line of the last character string displayed in the keyword area 2106, and the cursor is displayed at the start of the new last line. This
10   allows the operator to input a new keyword. Note that a newly input character string is displayed in, for example, red.

When a place other than the keyword area 2106 is clicked with the mouse 209, keyword inputting/editing
15   operation is terminated, and the keyword input/edited in red is stored in "keyword" of the condition information in the search condition list 607 which corresponds to the selected region in the image condition area 2104. When the processing is complete,
20   the flow advances to step S501. If there are a plurality of keyword contents, character strings expressing the contents are delimited with "," and input. In the above embodiment, red and black are used as an example. However, the present invention may be
25   applied to other combinations of colors. Character strings may be discriminated by using, for example, normal characters and underlined characters or shaded

- 60 -

character as well as different colors.

Similarity calculation processing in step S404 will be described next with reference to Figs. 12 and 19.

5   Fig. 12 is a view showing an example of the data arrangement of the region comparison buffer 608 in which the result obtained by comparison with the search condition designated in step S401 with respect to the region in the image which is extracted in step S402.

10   As shown in Fig. 12, the region ID of a region exhibiting the highest similarity with respect to each condition information in the search condition list 607 is stored in "region ID". This similarity is stored in "individual condition similarity", and the condition

15   number of the condition information is stored in "condition number".

Fig. 19 is a flow chart for explaining similarity calculation processing in step S404. First of all, the value of "similarity" in which the similarity between

20   the search condition list 607 and the image extracted in step S402 is stored is initialized by storing "0" in "similarity" (step S601). The contents of the region comparison buffer 608 are also cleared.

The value of "individual similarity" in which the

25   similarity between condition information in the search condition list 607 and the region in the image extracted in step S402 is stored is initialized by

storing "0" in "individual similarity". Pieces of
condition information are extracted one by one from the
start of the search condition list 607 (step S602). A
branch then occurs to the subsequent processing

5   depending on whether any condition information is
extracted (step S603). If any condition information
can be extracted (Yes), the flow advances to step S604.
If all the pieces of condition information are
extracted from the search condition list 607 (No), the

10   flow advances to step S609.

In step S604, pieces of region information about
the image extracted in step S402 are extracted from the
region database 606 one by one. If any region
information can be extracted in step S605 (No), the

15   flow advances to step S606. If all the pieces of
region information about the image extracted in step
S402 are extracted (Yes), the flow advances to step
S607.

In step S606, a similarity Sim between the

20   condition information extracted in step S602 and the
region information extracted in the image search
program 604 is calculated, and the value of "individual
similarity" is replaced with the calculated value of
the similarity Sim if the calculated value of the

25   similarity Sim is larger than the value stored in
"individual similarity". Note that when the value of
"individual similarity" is to be updated, the region ID

CFM03447/P204-0006

of the region information extracted in step S604 is
stored as "region candidate".

In this case, the similarity Sim is calculated by
one of the following three calculation methods
5   depending on the type stored in the condition
information extracted in step S602.
(1) If all the pieces of information are stored,
       Sim = ((w1 x S1) + (w2 x S2) + (w3 x S3) + (w4 x
           S4))/(w1 + w2 + w3 + w4)
10   (2) If the information of "keyword" is not stored,
       Sim = ((w2 x S2) + (w3 x S3) + (w4 x S4))/(w2 +
           w3 + w4)
(3) If the information of "region coordinates" is not
stored,
15   Sim = S1
where S1, S2, S3, and S4 are a keyword similarity,
color feature amount similarity, size similarity, and
position similarity, respectively, and w1, w2, w3, and
w4 are weights for the respective types of
20   similarities.

The keyword similarity S1 is calculated from
"keyword" in the condition information extracted in
step S602 and "keyword" in the region information
extracted in step S604. Since a plurality of character
25   strings are stored while being delimited with ",", all
combinations thereof will be compared. If there are
character strings which perfectly match with each

other, the value of S1 is set to "1.0". Since

character strings may be formed from natural sentences,

any character strings which perfectly match each other

may not be found. In this case, morphemic analysis of

5   character strings is performed to divide the character

strings into words to extract only nouns, adjectives,

and verbs as words. Character strings constituted by

theses words are then compared with each other. The

value obtained by dividing the number of words that

10   match with each other upon comparison by the number of

words used for the comparison is set as the value of

S1.

The color feature amount similarity S2 is

calculated from "color feature amount" in the condition

15   information extracted in step S602 and "color feature

amount" in the region information extracted in step

S604. Since the total histogram frequency is

normalized with 1,000, the color feature amount

similarity S2 can be obtained from the sum of the

20   absolute values of the differences between the

respective elements of "color feature amount".

$$S2 = 1 - (\Sigma \, | \, h1i - h2i \, |)/2000$$

where h1i is the ith element of "color feature amount"

in the condition information extracted in step S602,

25   and h2i is the ith element in "color feature amount" in

the region information extracted in step S604.

The size similarity S3 is calculated from "region

- 64 -

coordinates" in the condition information extracted in step S602 and "region coordinates" in the region information extracted in step S604. A method of calculating a size similarity from the area of a

5   polygon as a region can be listed as a known technique. For the sake of simplicity, a method of calculating a size similarity from the area of a rectangle circumscribed to a region is used.

       A circumscribed rectangle can be simply obtained

10   by obtaining the minimum and maximum x- and y-coordinates from "region coordinates" in the respective steps. "Region coordinates" in the condition information extracted in step S602 are the coordinates in the image condition area 2104, and

15   differ in scale from the image stored in the image database 605. If the numbers of pixels of the image condition area 2104 in the vertical and horizontal directions are both 120, the area of the region information is adjusted in scale in the following

20   manner:

       (area of region information) $\leftarrow$ (area of region information) x ((120 x 120)/((vertical size of image) x (horizontal size of image)))

       The vertical and horizontal sizes of the image

25   can be obtained from the image database 605.

       Subsequently, the size similarity S3 can be calculated as follows:

(1) If the area of the region information is larger than that of the condition information,

S3 = 1 - ((area of condition information)/(area of region information))

5 (2) If the area of the region information is smaller than the area of the condition information,

S3 = 1 - ((area of region information)/(area of condition information))

In addition, the position similarity S4 is
10 calculated from "region coordinates" in the condition information extracted in step S602 and "region coordinates" in the region information extracted in step S604. A method of calculating a position similarity from the center of gravity of a polygon as a
15 region can be listed as a known technique. In this case as well, for the sake of simplicity, a method of calculating a position similarity from the center of gravity of a rectangle circumscribed to a region is used.

20   A circumscribed rectangle can be simply obtained in the above manner. As in the case wherein a size similarity is obtained, the coordinates of the gravity of center of region information are corrected to be adjusted in scale in the following manner.

25   (x-coordinate of region information) ←
(x-coordinate of region information) x (120/(horizontal size of image))

- 66 -

(y-coordinate of region information) ←

(y-coordinate of region information) x (120/(vertical

size of image))

The position similarity S4 can be calculated

5   afterward as follows:

S4 = 1 - ((distance between condition information

and center of gravity of region

information)/(120 x $\sqrt{2}$))

When the processing in step S606 is complete, the

10 flow advances to step S604.

Step S607 is the processing of registering the

result obtained by comparison in steps S604 to S606 in

the region comparison buffer 608. If the value of

"individual similarity" is not 0, the value of the

15 condition number of the condition information extracted

in step S602 is stored in "condition number"; the value

of "region candidate", in "region ID"; and the value of

"individual similarity", in "individual condition

similarity". If the value of "individual similarity"

20 is 0, no information is registered in the region

comparison buffer 608. When the processing is

complete, the flow advances to step S608. In step

S608, the value of "individual similarity" is added to

"similarity", and the flow advances to step S602.

25   Step S609 is the processing of normalizing the

value stored in "similarity" with the number of pieces

of condition information stored in the search condition

- 67 -

list 607. In this case, the value stored in
"similarity" is replaced with the value obtained by
dividing the value stored in "similarity" by the number
of pieces of condition information. When the
5   processing is complete, the similarity calculation
processing is terminated.

Thumbnail generation processing in step S406 will
be described next with reference to Fig. 20. Fig. 20
is a flow chart for explaining in detail the thumbnail
10   generation processing in step S406.

A rectangular region enclosing a region of the
regions stored in the region comparison buffer 608
which has no parent region in the search condition list
607 is generated on the image extracted in step S402
15   (step S701). More specifically, the region IDs stored
in the region comparison buffer 608 are extracted one
by one, and the minimum x- and y-coordinates and
maximum x- and y-coordinates of only a region whose
value of "parent region" corresponding to the search
20   condition list 607 is "-1" are obtained from the
corresponding region coordinates in the region database
606 on the basis of the corresponding condition number.
This makes it possible to obtain a rectangular region
circumscribed to the region. In this case, since
25   rectangular regions are synthesized to generate
thumbnails, a rectangular region larger than the
circumscribed region is generated. A target

- 68 -

rectangular region can be generated by subtracting predetermined values from the minimum x- and y-coordinates and adding predetermined values to the maximum x- and y-coordinates. Obviously, these

5 calculations make the coordinate values fall within the image.

If, for example, regions with the region IDs "100001" and "100002" exist in the region comparison buffer 608 with respect to the image shown in Fig. 8,

10 rectangular regions surrounding the car and house as shown in Fig. 24A can be obtained from the region database 606 shown in Fig. 10. Figs. 24A to 24C are views for explaining how thumbnail generation processing according to an embodiment is performed. If

15 regions with the region ID "100001" and "100003" exist in the region comparison buffer 608, rectangular regions surrounding the car and tree can be obtained, as shown in Fig. 25A. Figs. 25A to 25C are views for explaining how thumbnail generation processing

20 according to another embodiment is performed.

In step S702, rectangular regions which are obtained in step S701 and overlap each other are integrated. Whether two rectangular regions overlap each other can be easily determined by comparing the

25 minimum x- and y-coordinates and maximum x- and y-coordinates of the two rectangular regions. If the two rectangular regions overlap each other, smaller

values of the minimum x- and y-coordinates of the two

regions are set as the minimum x- and y-coordinates of

the new rectangular region. Likewise, larger values of

the x- and y-coordinates of the two regions are set as

5   the maximum x- and y-coordinates of the new rectangular

region.

Regions are continuously integrated by repeatedly

comparing two regions in this manner. When region

integration cannot be done anymore, the flow advances

10   to step S703. If, for example, the two rectangular

regions shown in Fig. 24A exist, the rectangular region

shown in Fig. 24B is generated as a result of

integration.

In step S703, the position of each rectangular

15   region on a thumbnail image which has been obtained in

the processing up to step S702 is determined.

According to the simplest method, the minimum

rectangular region including all the rectangular

regions obtained in the processing up to step S702 is

20   obtained, and the obtained region is used as a

thumbnail image. Such a rectangular region can be

obtained by obtaining the minimum x- and y-coordinates

from the respective rectangular regions, setting the

obtained coordinates as the coordinates of the upper

25   left point of the rectangular region, obtaining the

maximum x- and y-coordinates, and setting the obtained

coordinates as the coordinates of the lower right point

of the rectangular region.

In this embodiment, since the maximum horizontal and vertical sizes of a thumbnail image are both set to 120 pixels, it suffices if the rectangular region is
5   reduced or enlarged such that the size of a longer one of the vertical and horizontal sizes of the rectangular region is set to 120 pixels. With this operation, on the thumbnail image, both the x- and y-coordinates of the upper left point of the rectangular region
10   including all the rectangular regions become 0, and one or both of the x- and y-coordinates of the lower right point become 120. With this processing, if, for example, the rectangular region shown in Fig. 24B is obtained in step S702, the arrangement of the
15   rectangular region on the thumbnail image becomes the one shown in Fig. 24C. If the rectangular regions shown in Fig. 25A are obtained, the arrangement of the rectangular regions on the thumbnail image become those shown in Fig. 27. When the processing is complete, the
20   flow advances to step S704. Fig. 27 is a view for explaining the thumbnail image generation result obtained by thumbnail generation processing.

In step S704, coordinates indicating a region on a thumbnail image which is stored in the region
25   comparison buffer 608 are obtained by converting the region coordinates stored in the region database 606. Assume that the minimum rectangular region which is

obtained in step S703 and includes all the rectangular regions is long from side to side. In this case, letting x0 be the x-coordinate value of the upper left point of this rectangular region, y0 be the

5   y-coordinate value of the region, x1 be the horizontal size of the region, x be the x-coordinate of the region coordinates stored in the region database 606, and y be the y-coordinate of the region coordinates, an x-coordinate x' and y-coordinate y' of the region

10   coordinates on the thumbnail after conversion can be obtained by

$$x' = (120/x1)x - x0$$
$$y' = (120/x1)y - y0$$

If the rectangular region is longer than wide,

15   the region coordinates can be converted in the same manner as described above. The region coordinates obtained in this case are stored in "region coordinates" in the search result list 609. When the processing is complete, the flow advances to step S705.

20   Step S705 is the processing of synthesizing a thumbnail image. According to the above rectangular region arranging method, the minimum rectangular region enclosing all rectangular regions itself becomes a thumbnail image. In addition, each region on the

25   thumbnail image is edged with thick lines in a color determined in advance by a search number with respect to the regions stored in the region comparison buffer

608 on the basis of "region coordinates" of each region
on the thumbnail image obtained in step S704.

Referring to Fig. 24C, for example, the car is
edged with the solid lines, whereas the house is edged
5 with the broken lines. This indicates that these lines
differ in color. Obviously, regions can be edged with
different kinds of lines such as solid lines, dotted
lines, and double lines instead of being displayed in
different colors for the respective condition numbers.
10 If regions are displayed in different forms so as to
discriminate the regions for the respective condition
numbers, the same effect as that described above can be
obtained. When the processing is complete, the
thumbnail generation processing is terminated.
15 According to the above thumbnail generation
method, as shown in, for example, Fig. 27, when the
regions stored in the region comparison buffer 608
exist at two ends, the regions satisfying search
conditions may also be displayed small on the thumbnail
20 image displayed as a search result. Another thumbnail
generation method for making an improvement for such a
case will be described below.

Basically, this method is executed by the same
sequence as that shown in the flow chart of Fig. 20.
25 However, when the arrangement of the rectangular
regions generated in step S701 is determined in step
S703, the rectangular regions are arranged after

regions corresponding to the x-coordinate and
y-coordinate values which are not used by the
rectangular regions are removed. The x-coordinate and
y-coordinate values which are not used by the
5   rectangular regions can be easily obtained by
projecting all the rectangular regions on the x- and
y-axes and considering the inclusive relationship
between the regions on the x- and y-axes.

        If, for example, the rectangular regions shown in
10   Fig. 25A are generated in step S701, the regions
displayed in dots in Fig. 25B are regions corresponding
to the x-coordinate and y-coordinate values which are
not used by the rectangular regions. If the
rectangular regions are arranged upon removal of such
15   regions, they are arranged as shown in Fig. 25C. In
the region coordinate conversion processing in step
S704, since the coordinates of the upper left point of
each rectangular region on the thumbnail image can be
known, the region coordinates can be easily converted
20   in the same manner as described above.

        In the thumbnail image synthesis processing in
step S705, the rectangular regions are arranged on the
thumbnail image on the basis of the arrangement of the
respective rectangular regions determined in step S703,
25   and the regions which have not been removed in step
S703 are arranged on the thumbnail image in the same
manner, thereby synthesizing a thumbnail image. For

example, the image shown in Fig. 24A becomes the one

shown in Fig. 24C as a thumbnail image.

According to the above thumbnail generation

method, if the regions stored in the region comparison

5   buffer 608 greatly differ in size, a smaller region is

not displayed large. This may make it difficult to

visually check the region. Still another thumbnail

generation method for making an improvement for such a

case will be described below.

10   Basically, this method is executed by the same

sequence as that shown in the flow chart of Fig. 20.

If a plurality of rectangular regions are present after

the formation of a rectangular region surrounding the

regions stored in the region comparison buffer 608 in

15   step S701, integration of the rectangular regions in

step S702 is not performed. Instead of this operation,

the rectangular regions are enlarged or reduced such

that the respective rectangular regions have the same

area.

20   For example, the area of the largest rectangular

region is obtained, and the areas of other rectangular

regions are increased to become equal to the area of

the largest rectangular region. In this case, the

values of "region coordinates" stored in the region

25   database 606 in correspondence with the coordinates of

the vertexes of polygonal regions included in the

respective rectangular regions are converted in advance

into coordinates with the upper left point of each
rectangular region being set as an origin. This
processing can be implemented by using the same method
as that described in association with step S704.

5   Obviously, it also suffices to make target regions
themselves have the same area instead of making
rectangular regions have the same area.

Subsequently, as in step S703, the arrangement of
the rectangular regions on the thumbnail image is

10   determined. Rectangular regions made to have the same
area are sequentially extracted starting from one of
the rectangular regions generated in step S701 whose
x-coordinate and y-coordinate values of the coordinates
of the upper left point are smallest, and the

15   rectangular regions are sequentially arranged from the
upper left point of an image to be synthesized such
that the synthetic image to be finally generated has an
area as small as possible.

For example, after the first rectangular region

20   is placed, the second and subsequent rectangular
regions are arranged in the following manner. The
upper left point of a polygon synthesized by already
arranged rectangular regions is set as an origin, and a
search is made from a vertex, other than the origin,

25   having 0 as an x-coordinate value to a vertex having 0
as a y-coordinate value. The upper left point, upper
right point, and lower left point of the rectangular

region to be placed are matched with vertexes under
search, thereby obtaining the placement position of the
rectangular region at which the coordinate value of the
vertex of the rectangle to be placed is equal to or

5 larger than 0, the rectangular region does not overlap
the polygon synthesized by already arranged rectangular
regions, and the area of a rectangle circumscribed to a
polygon to be synthesized after placement is minimized.

For example, the rectangular regions of the tree

10 and car shown in Fig. 25A are so arranged as to have
the same area, as shown in Fig. 26. Fig. 26 is a view
for explaining how thumbnail image generation
processing is performed when the areas of a plurality
of rectangular regions are made uniform. A rectangle

15 circumscribed to the rectangular regions arranged in
this manner is a basis of a thumbnail image. The image
is reduced or enlarged to make a long side of the
circumscribed rectangle have a length of 120 pixels,
thereby generating a thumbnail image.

20 In step S704, coordinates representing a region
stored in the region comparison buffer 608 are obtained
on the basis of the region coordinates of a region in
the rectangle obtained in step S701. The coordinates
of the upper left vertex of a rectangular region

25 surrounding the respective regions on a thumbnail image
can be easily obtained in this manner, and hence can be
easily obtained by the same method as that described in

association with step S704. Thereafter, a thumbnail
image is synthesized by the same method as that
described in association with step S705.

The above thumbnail generation method displays
5   only the regions stored in the region comparison buffer
608 without displaying the entire image, and hence the
operator may not grasp the entire image. If, for
example, a thumbnail like the one shown in Fig. 24C is
generated, the tree is not displayed, as seen from
10   Fig. 24A. If the thumbnail shown in Fig. 26 is
generated, the house is not displayed. Still another
thumbnail generation method for making an improvement
for such a case will be described below.

In this case, a plurality of thumbnail images are
15   generated unlike in the prior art wherein only one
thumbnail is generated. One thumbnail image is an
image obtained by reducing an image in the image
database 605. This image is reduced such that the size
of a longer side, either the vertical size or the
20   horizontal size, becomes 120 pixels. As in step S704,
the contour of each region on a thumbnail image, which
is stored in the region comparison buffer 608, is edged
with thick lines in a color determined by the search
number. As other thumbnail images, thumbnail images
25   are generated one by one with respect to regions of the
regions stored in the region comparison buffer 608
which have no parent region in the search condition

list 607. The method of generating these thumbnail images basically takes the same sequence as that in the flow chart of Fig. 20, but there is no need to perform the rectangular region integration in step S702.

5   In the rectangular region arrangement determination processing in step S703, the aspect ratio of a thumbnail image to be generated is made equal to that of an image in the image database 605. The two vertical or horizontal sides of this thumbnail image

10   are aligned with the corresponding two sides of the rectangular region generated in step S701. When, however, an image in the image database 605 is extracted in the form of a rectangle as a thumbnail image based on this positional relationship, and the

15   outside of the image in the image database 605 is extracted, the position of the rectangle as the thumbnail image and the position of the rectangular region generated in step S701 are shifted and corrected such that the extracted image is located inside.

20   In step S704, the coordinates of the rectangular region can be converted in the same manner as described above. In step S705, on the image in the image database 605, a thumbnail image is extracted from the image in the image database 605 on the basis of the

25   positional relationship between the rectangular region generated in step S701 and the rectangle of the thumbnail image determined in step S703, and the

extracted image is reduced such that the size of a

longer one of the vertical and horizontal sizes becomes

120 pixels. As described above, then, the contour of

the region on the thumbnail image is edged with thick

5   lines in a color determined by the search number.

If, for example, regions with the region IDs

"100001" and "100003" are present in the region

comparison buffer 608 with respect to the image shown

in Fig. 8, the thumbnail image obtained by reducing the

10   image in the image database 605 becomes the one shown

in Fig. 28A. Figs. 28A to 28C are views for explaining

an embodiment of thumbnail generation processing of

generating a plurality of thumbnails with respect to

one image. In addition, a thumbnail image

15   corresponding to the region ID "100001" becomes the one

shown in Fig. 28B, and a thumbnail image corresponding

to the region ID "100003" become the one shown in

Fig. 28C.

When a plurality of thumbnail images are to be

20   generated with respect to one image in this manner,

"thumbnail image" in the search result list 609 is

extended to generate a plurality of thumbnail images.

For example, each file name is quoted with """, and the

file names quoted with """ are delimited with ",",

·25   thereby allowing a plurality of thumbnail images to be

stored. The file names are sequentially stored in

"thumbnail image", starting from the thumbnail image

obtained by reducing the image in the image database 605, followed by a thumbnail image corresponding to the first region ID in the region comparison buffer 608.

In step S408, when thumbnail images are to be
5   displayed in the search result display area 2103, a plurality of thumbnail images may be automatically and sequentially displayed in an alternate manner like a slide show. When the switching button 2110 is repeatedly clicked with the mouse 209 in step S409,
10 images are displayed in the search result display area 2103 by the same display method as that described in association with step S409. In this case, each thumbnail is displayed in the search result display area 2103 while the mode of automatically and
15 alternately displaying thumbnails is inhibited. At first, the thumbnail image obtained by reducing the image in the image database 605 is displayed. Every time the switching button 2110 is clicked, a thumbnail including the region indicated by the region ID in the
20 region comparison buffer 608 which corresponds to a target condition number is displayed, and the thick lines of the region are blinked. When thumbnail images corresponding to all the condition numbers are alternately displayed, the state wherein thumbnail
25 images are automatically and sequentially displayed in an alternate manner is restored.

When a plurality of thumbnail image are generated

with respect to one image in this manner, these

thumbnail images may be simultaneously displayed side

by side in the search result display area 2103. In

this case, the adjacent thumbnail images need to be

5   surrounded with thick lines to allow the operator to

know that they are thumbnails with respect to the same

image.

Note that this embodiment has exemplified the

case wherein the image registration program and image

10   search program are directly loaded from the CD-ROM as

an external storage device into the RAM 203 to be

executed. Alternatively, the image registration

program and image search program may be temporarily

stored (installed) from the CD-ROM into the hard disk

15   drive 206, and may be loaded from the hard disk drive

206 into the RAM 203 when they are executed.

As a medium for recording the image registration

program and image search program, an FD (Flexible

Disk), IC memory card, or the like may be used instead

20   of the CD-ROM.

In addition, the image registration program and

image search program may be recorded on the ROM 202 as

part of the memory map so as to allow the CPU 201 to

directly execute them.

25   Furthermore, the image registration program and

image search program may be stored in a server on a

network, and may be downloaded from the server on the

network into the RAM 203 through the network card 210 as needed.

This embodiment has exemplified the embodiment of making a search for a still image stored in the image
5   database 605. In addition to the image database 605, however, a moving image database may be prepared. Still images of a plurality of key frames are then made to correspond to each moving image data and stored in the image database 605. The above method is used to
10   search for a key frame stored in the image database 605 to search for a corresponding moving image. In this case, in addition to a key frame, a position from the start of the moving image corresponding to the key frame on the time axis may be stored to allow playback
15   of the moving image from the position on the time axis after the key frame is searched out.

In this embodiment, similarities with search conditions are calculated by using colors and the sizes and positions of regions as image features of the
20   regions. However, since the region coordinates stored in the region database 606 themselves represent the shapes of the regions, the shape of each region may be used to calculate a similarity with a search condition.

In this embodiment, the contour of a region is
25   expressed by a polygon, and the coordinates of the vertexes of the polygon are stored in "region coordinates" in the region database 606. However, a

region may be expressed in the form of a rectangle

circumscribed to the region, and only the coordinates

of the upper left and lower right points of the

rectangle circumscribed to the region may be stored.

5   This makes it possible to reduce the storage capacity

for region coordinates in the region database 606.

In this embodiment, "keyword" is stored in the

region information in the region database 606 to

express the contents of a region. However, a concept

10 code corresponding to the contents of a region may be

stored instead of a keyword. In this case, a concept

code is, for example, a unique number assigned to each

node in a thesaurus that expresses a concept system in

the form of a tree structure.

15   More specifically, in the keyword setting

processing in step S203, a list of nodes (concepts) in

the thesaurus is displayed to allow selection of a

desired concept. The selected concept is then stored

in the region database 606. Alternatively, the

20 thesaurus may be searched by using a keyword input in

the keyword setting processing in step S203 as a key to

obtain a concept code corresponding to the keyword, and

the obtained code may be stored in the region database

606. Concept codes are stored instead of keywords of

25 condition information in the search condition list 607.

A keyword input or edited in step S508 can be replaced

with a concept code in the same manner as described

above and stored in the search condition list 607.
When the similarity Sim is calculated in step S606, a
concept code similarity is used instead of a keyword
similarity. If concept codes coincide with each other,
5   the concept code similarity is set to "1.0".

In this embodiment, basically, as a thumbnail
image corresponding to an image extracted in step S402,
a partial image of the image or an image obtained by
synthesizing regions is used instead of an image
10   obtained by simply reducing the extracted image. If
the ratio of the area of the region stored in the
region comparison buffer 608 to the area of the image
is equal to or higher than a predetermined ratio, an
image obtained by simply reducing the image may be used
15   as a thumbnail image.

In this embodiment, with regard to a target
image, a thumbnail image is synthesized in step S705 by
using a rectangular partial image circumscribed to a
region, and hence the partial image outside the region
20   is included in the thumbnail image. For this reason, a
thumbnail image may be synthesized by using only an
image within a region without using any partial image
outside the region.

In this embodiment, a thumbnail image is
25   generated in step S406. Assume, however, that
complicated regions are not synthesized. In this case,
only the coordinates of·a rectangular region to be

displayed in the search result display area 2103 may be

stored with respect to a target image, and only a

partial image of the target image may be displayed on

the basis of the stored coordinates when a thumbnail

5   image is displayed in the search result display area

2103 in step S408.

In this embodiment, a thumbnail image is

generated in step S406. However, thumbnail images may

be generated in advance with respect to all

10   combinations of registered regions before the image

registration program is terminated after step S211, and

a thumbnail image corresponding to the region stored in

the region comparison buffer 608 may be obtained by a

search instead of step S406.

15   This embodiment has exemplified the case wherein

only one region exhibiting the highest similarity with

each condition information in the search condition list

607 can be registered in the region comparison buffer

608. However, the embodiment may allow a plurality of

20   regions equal to or higher than a specific threshold

may be registered with respect to one condition

information. In order to allow this operation, a

plurality of "individual similarity" and "region

candidate" fields, which are used in the similarity

25   calculation processing in step S404, are prepared in

the form of an array. If the value of the similarity

Sim calculated in step S606 is larger than a specific

threshold, the value of Sim and the region ID are stored in the array of "individual similarity" and "region candidate" fields. In step S607, the information stored in the array of "individual

5 similarity" and "region candidate" fields is registered in the region comparison buffer 608.

As described above, the image search apparatus according to the present invention includes the image storage unit 101 which stores a plurality of images,

10 the region information storage unit 102 which stores specific partial images included in the respective images stored in the image storage unit 101 in correspondence with the respective images, and the region feature storage unit 103 which stores features

15 of the partial image stored in the region information storage unit 102 in correspondence with the partial images. The image feature designation unit 104 designates a feature of a search target image. The candidate image decision unit 105 searches the features

20 of the partial images stored in the region information storage unit 102 on the basis of the designated image feature, and determines an image as a candidate image among the image stored in the image storage unit 101 which is associated with the partial image obtained on

25 the basis of the search result. The search result display unit 106 is characterized in that a partial image included in the determined candidate image is

enlarged to a predetermined size, and a reduced image of the candidate image is displayed.

The image search apparatus according to the present invention is characterized in that when a

5 plurality of candidate images are obtained on the basis of a search result, the search result display unit 106 displays a list of reduced images of the plurality of candidate images.

The image search apparatus according to the

10 present invention is also characterized in that the search result display unit 106 displays reduced images within an area having a predetermined size.

In addition, the image search apparatus according to the present invention is characterized in that a

15 partial image is a rectangular image having a region surrounded with a circumscribed rectangle of a predetermined object region included in an image.

Furthermore, the image search apparatus according to the present invention is characterized in that the

20 search result display unit 106 displays a reduced image of a candidate image while emphasizing a partial image included in the candidate image.

Moreover, the image search apparatus according to the present invention is characterized in that a

25 feature of an image is at least one of concept information expressing a concept obtained from a partial image, language information expressing the

concept in a language, an image feature expressing a feature of a partial image, and a combination of concept information, language information, and an image feature.

5   As described above, according to this embodiment, since the search result display unit 106 displays a region whose feature is determined to be identical or similar to a designated feature or a partial image including the region while emphasizing it to make it

10   easy to visually identify it among images obtained as a search result, a region (object or the like) that satisfies a search condition can be easily found.

If a plurality of such regions are present among images obtained as a search result, the search result

15   display unit 106 alternately displays the regions to be emphasized or partial images including the regions while emphasizing them to make it easy to visually identify them among images obtained as a search result. This makes it possible to easily search for a region

20   (object or the like) that satisfies a search condition.

In addition, the search result display unit 106 displays regions which are determined by the candidate image decision unit 105 to identical or similar to a feature selected by the image feature selection unit or

25   partial images including the regions while switching targets to be emphasized. This makes it possible to easily search for a region (object or the like)

corresponding to an individual search condition.

Furthermore, as described above, the search result display unit 106 makes it easy to search for a region satisfying a search condition in an image

5 obtained as a search result with respect to one candidate image. Therefore, as shown in Fig. 21, when a plurality of candidate images are displayed in the form of a list, a region that satisfies a search condition can be easily found, in particular. This

10 improves the search operation efficiency.

<Second Embodiment>

An outline of an image search apparatus according to the second embodiment of the present invention will be described first. The arrangement of the image

15 search apparatus according to the second embodiment of the present invention is the same as that of the image search apparatus according to the first embodiment shown in the block diagram of Fig. 1. However, a search result display unit 106 displays a partial image

20 of a candidate image which is determined by a candidate image decision unit 105 and includes a plurality of regions whose features are determined to be identical or similar to a designated feature. The search result display unit 106 also displays images of a plurality of

25 regions or an image obtained by synthesizing partial images including these regions.

In addition, the search result display unit 106

displays an image which is synthesized such that the
relative positional relationship between a plurality of
regions is maintained. The search result display unit
106 also displays an image which is synthesized such
5   that these regions have the same size. Furthermore,
the search result display unit 106 displays an image of
a region or an image including a region to make it easy
to visually recognize the position of the image.

The operations of the search result display unit
10   106 and the remaining units in the image search
apparatus having the above arrangement are the same as
those described in the first embodiment. The image
search apparatus according to the present invention
includes an image storage unit 101 which stores a
15   plurality of images, a region information storage unit
102 which stores predetermined partial images included
in the respective images stored in the image storage
unit 101 in correspondence with the respective images,
and a region feature storage unit 103 which stores
20   features of the partial images stored in the region
information storage unit 102 in correspondence with the
partial images. An image feature designation unit 104
designates a feature of an image as a search target.
The candidate image decision unit 105 searches for
25   features of partial images stored in the region feature
storage unit 103 on the basis of the designated image
feature, and determines an image made to correspond to

the plurality of partial images obtained on the basis of the search result as a candidate image from the images stored in the image storage unit 101. The search result display unit 106 then enlarges a

5 plurality of partial images included in the determined candidate image to a predetermined size and displays a reduced image of the candidate image.

The image search apparatus according to the present invention is characterized in that the search

10 result display unit 106 synthesizes a plurality of partial images to generate a new partial image, and displays the new partial image as a reduced image.

The image search apparatus according to the present invention is characterized in that the search

15 result display unit 106 synthesizes a plurality of partial images to generate a new partial image while keeping the relative positional relationship between the plurality of partial images.

The image search apparatus according to the

20 present invention is also characterized in that when a plurality of partial images partly overlap each other, the search result display unit 106 synthesizes the plurality of partial images to generate a new partial image.

25 The image search apparatus according to the present invention is further characterized in that the sizes of a plurality of partial images are unified to a

predetermined size.

As described above, according to the image search apparatus of this embodiment, the search result display unit 106 displays a partial image of a candidate image
5   including a plurality of regions satisfying the search condition designated by the image feature designation unit 104 as a search result image. This makes it easy to find a region (object or the like) satisfying the search condition. In addition, the states of the
10   details of the region can be easily grasped.

In addition, the search result display unit 106 displays images of a plurality of regions or an image obtained by synthesizing partial images including these regions as a search result image. This makes it easy
15   to find a region (object or the like) satisfying the search condition. In addition, the states of the details of the region can be easily grasped.

Furthermore, since the search result display unit 106 displays an image which is so synthesized as to
20   keep the relative positional relationship between a plurality of regions, the relationship between the regions can be easily grasped in the entire image.

Moreover, the search result display unit 106 displays an image as a search result image which is
25   synthesized such that a plurality of region images or partial images including the region images have the same or almost the same size. Even if, therefore, the

respective regions in the image greatly differ in size, a region (object or the like) which satisfies a search condition can be easily found. In addition, the states of the details of the region can be easily grasped.

5   <Third Embodiment>

An outline of an image search apparatus according to the third embodiment of the present invention will be described next. The arrangement of the image search apparatus according to the third embodiment of the

10   present invention is the same as that of the image search apparatus according to the first embodiment shown in the block diagram of Fig. 1. However, a search result display unit 106 displays a plurality of reduced images as search result images with respect to

15   one candidate image determined by a candidate image decision unit 105.

As described in the first embodiment, one thumbnail image is an image obtained by reducing an image in an image database 605 such that the size of a

20   longer one of the vertical and horizontal sizes of the region becomes 120 pixels. As in step S704, with regard to the regions stored in a region comparison buffer 608, the contours of respective regions on a thumbnail image are edged with thick lines in colors

25   determined by search numbers. As other thumbnail images, thumbnail images are generated one by one with respect to regions, of the regions stored in the region

comparison buffer 608, which have no parent regions in a search condition list 607. A method of generating such thumbnail images basically takes the same sequence as that in the flow chart shown in Fig. 20. However,

5   there is no need to perform rectangular region integration in step S702.

In addition, the search result display unit 106 includes, in a plurality of search result images with respect to one candidate image, partial images of the

10   candidate image including regions whose features are determined by the candidate image decision unit 105 to be identical or similar to a designated feature. The search result display unit 106 also includes the candidate image in a plurality of search result images

15   with respect to one candidate image. The search result display unit 106 also displays a plurality of search result images with respect to one candidate image in the same or almost same size.

Furthermore, the search result display unit 106

20   alternately displays a plurality of search result images with respect to one candidate image at the same position in accordance with an instruction from a switching unit (not shown). The search result display unit 106 alternately displays a plurality of search

25   result images with respect to one candidate image in an automatic manner. In addition, the search result display unit 106 displays a region whose feature is

determined by the candidate image decision unit 105 to be identical or similar to a designated feature or a partial image including the region so as to make it easy to visually identify it among search result

5   images.

The operations of the search result display unit 106 and the remaining units in the image search apparatus having the above arrangement are the same as those described in the first embodiment. The image

10 search apparatus according to the present invention includes an image storage unit 101 which stores a plurality of images, a region information storage unit 102 which stores predetermined partial images included in the respective images stored in the image storage

15 unit 101 in correspondence with the respective images, and a region feature storage unit 103 which stores features of the partial images stored in the region information storage unit 102 in correspondence with the partial images. An image feature designation unit 104

20 designates a feature of an image as a search target. The candidate image decision unit 105 searches for features of partial images stored in the region feature storage unit 103 on the basis of the designated image feature, and determines an image made to correspond to

25 the plurality of partial images obtained on the basis of the search result as a candidate image from the images stored in the image storage unit 101. The

search result display unit 106 is characterized by
displaying a reduced image of a determined candidate
image in a plurality of patterns.

The image search apparatus according to the
5   present invention is characterized in that the search
result display unit 106 displays a list of a plurality
of reduced images.

The image search apparatus according to the
present invention is characterized in that the search
10   result display unit 106 displays a reduced image of a
candidate image.

The image search apparatus according to the
present invention is characterized in that the search
result display unit 106 displays a reduced image of a
15   partial image used to determine a candidate image.

The image search apparatus according to the
present invention is characterized in that the search
result display unit 106 alternately displays reduced
images one by one at the same position in an automatic
20   manner.

The image search apparatus according to the
present invention is characterized in that the
apparatus further includes a switching unit for
alternate display of reduced images, and the search
25   result display unit 106 alternately displays the
reduced images one by one at the same position.

As described above, according to the image search

apparatus of this embodiment, the search result display
unit 106 displays a plurality of images as search
result images with respect to one candidate image,
while the search result images includes images of

5   regions satisfying the search condition designated by
the image feature designation unit 104 or partial
images including the regions. Therefore, a region
(object or the like) that satisfies a search condition
can be easily found. In addition, the states of the

10   details of the region can be easily grasped.

In addition, since the search result display unit
106 includes the candidate image in a plurality of
search result images with respect to one candidate
image, the relationship between the regions in the

15   entire image can be easily grasped.

Furthermore, since the search result display unit
106 displays a plurality of search result images with
respect to one candidate image in the same or almost
the same size, a region (object or the like) satisfying

20   a search condition can be easily found. In addition,
the states of the details of the region can be easily
grasped.

Moreover, since the search result display unit
106 alternately displays a plurality of search result

25   images with respect to one candidate image at the same
position manually or automatically, a region (object or
the like) that satisfies a search condition can be

easily found. In addition, the states of the details of the region can be easily gasped, and the relationship between the regions in the entire image can be easily grasped.

5   <Other Embodiment>

In the above embodiments, the present invention is implemented in a stand-alone form. However, the present invention can be executed as services offered by a server on a network to allow a client machine to

10   use the function of the present invention.

Note that the present invention can be applied to an apparatus comprising a single device or to system constituted by a plurality of devices.

Furthermore, the invention can be implemented by

15   supplying a software program, which implements the functions of the foregoing embodiments, directly or indirectly to a system or apparatus, reading the supplied program code with a computer of the system or apparatus, and then executing the program code. In

20   this case, so long as the system or apparatus has the functions of the program, the mode of implementation need not rely upon a program.

Accordingly, since the functions of the present invention are implemented by computer, the program code

25   installed in the computer also implements the present invention. In other words, the claims of the present invention also cover a computer program for the purpose

of implementing the functions of the present invention.

In this case, so long as the system or apparatus has the functions of the program, the program may be executed in any form, such as an object code, a program
5 executed by an interpreter, or scrip data supplied to an operating system.

Example of storage media that can be used for supplying the program are a floppy disk, a hard disk, an optical disk, a magneto-optical disk, a CD-ROM, a
10 CD-R, a CD-RW, a magnetic tape, a non-volatile type memory card, a ROM, and a DVD (DVD-ROM and a DVD-R).

As for the method of supplying the program, a client computer can be connected to a website on the Internet using a browser of the client computer, and
15 the computer program of the present invention or an automatically-installable compressed file of the program can be downloaded to a recording medium such as a hard disk. Further, the program of the present invention can be supplied by dividing the program code
20 constituting the program into a plurality of files and downloading the files from different websites. In other words, a WWW (World Wide Web) server that downloads, to multiple users, the program files that implement the functions of the present invention by
25 computer is also covered by the claims of the present invention.

It is also possible to encrypt and store the

program of the present invention on a storage medium

such as a CD-ROM, distribute the storage medium to

users, allow users who meet certain requirements to

download decryption key information from a website via

5   the Internet, and allow these users to decrypt the

encrypted program by using the key information, whereby

the program is installed in the user computer.

Besides the cases where the aforementioned

functions according to the embodiments are implemented

10   by executing the read program by computer, an operating

system or the like running on the computer may perform

all or a part of the actual processing so that the

functions of the foregoing embodiments can be

implemented by this processing.

15   Furthermore, after the program read from the

storage medium is written to a function expansion board

inserted into the computer or to a memory provided in a

function expansion unit connected to the computer, a

CPU or the like mounted on the function expansion board

20   or function expansion unit performs all or a part of

the actual processing so that the functions of the

foregoing embodiments can be implemented by this

processing.

As many apparently widely different embodiments

25   of the present invention can be made without departing

from the spirit and scope thereof, it is to be

understood that the invention is not limited to the

specific embodiments thereof except as defined in the appended claims.

As has been described above, according to the present invention, when a search is made for an image by designating a keyword or object, the search result can be displayed more preferably. In addition, a desired image can be efficiently found from the displayed search result.

More specifically, a region in an image which corresponds to a feature designated as a search condition can be easily found from a search result, leading to an improvement in search operation efficiency. In addition, when candidate images as a result of a search are displayed in the form of a list, comparing partial images in the candidate images which satisfy a search condition makes it easy to determine which one of the candidate images is a desired image.

Furthermore, according to the present invention, the states of the details of a found region can be easily grasped, so the search operation efficiency can be improved.

Moreover, according to the present invention, when a plurality of search conditions are designated, the operator can easily grasp which object in a search result image corresponds to which search condition. This makes it possible to improve the search operation efficiency.

The present invention is not limited to the above embodiments and various changes and modification can be made within the spirit and scope of the present inventions. Therefore, to apprise the public of the

5   scope of the present invention, the following claims are made.